



# TOPFLOOR

## Acrytop acrylic system

### ACY CONCRETE EPOXY PRIMER

#### DESCRIPTION

TOPFLOOR concrete primer is a high strength epoxy coating on a concrete surfaces. TOPFLOOR concrete primer is a concentrated material that is diluted at the jobsite  
Basic use: TOPFLOOR concrete primer is designed to improve the adhesion of TOPFLOOR acrylic coating to concrete surfaces. **It should be considered that the concrete has the risk of moving. This causes crack in time. For this reason, we, as Topfloor, do not recommended the installation of sports floor in acrylic and polyurethane on the concrete base. TOPFLOOR recommended substrat for acrylic and PU systems is ASPHALT.**

#### APPLICATION

Be careful to fully coat the surface filling all voids but do not allow material to pool in low spots. Allow the primer to dry before proceeding with patching.

#### PACKAGING AND STORAGE

TOPFLOOR concrete primer is two components and available in 7+3 kg plastic drums. Should be stored at room temperature. Storage area climate condition should not be above 30C and below 10C . If stored in appropriate conditions, The shelf-life of TOPFLOOR concrete primer is 12 months from the date of manufacturer. material must be protected from freezing.

#### TECHNICAL DATA

**Product:** TOPFLOOR concrete primer

**Binder:** Epoxy

**Drying time:** 1 hr (25C) 2-6 hours wait for apply the second coat. Should be observed that the surface completely dry.

Theoretical consumption area: TOPFLOOR concrete primer theoretical area 250-300gr/m2.

